

FPT-55 Series

An ideal choice for budget conscious customers who require a reliable hand pallet truck.

CAPACITY

5500 lb (2487 kg) combined

OPERATION

- 180 degree operational arc.
- Requires thirteen full strokes to reach maximum elevated height of 7.8" (198mm)
- Control handle has three position (raise/neutral/lower) fingertip control
- Spring loaded handle returns to upright position automatically

HYDRAULICS

- Quality pump design complete with a special lowering valve allowing controlled rate of descent and an overload by-pass valve

FORKS / CHASSIS

- Tapered forks with ramped tips allow for easy pallet entry and exit
- Rugged heavy-duty frame
- Adjustable push rods allow for individual adjustment capability
- Hangers are constructed of cast iron for greater strength and longevity
- Easy maintenance
- Frame is powder coat paint

WARRANTY

- One year structural and one year hydraulic pump warranty



Easy Access Controls



Hydraulic Pump



Entry Ramp Tips

Designation	Model		FPT55 / 27 x 48	
	Load Capacity		5500 lb / 2487 kg	
Chassis Dimensions	Pallet Forks	Lowered Height	2.9"	73.66mm
		Fork Length	48"	1219mm
		Fork Width	6.5"	165.10mm
		Fork Spread	27"	685.8mm
	Lift Height	7.8"	198.12mm	
Approximate Shipping Weight		180 lbs	82 kg	
Wheels and Rollers	Steering Wheel	Polyurethane on Steel Hub	7" dia. x 2"	
			178mm dia. x 51mm	
	Load Rollers	Polyurethane	2.9" dia. x 3.6"	
73mm dia. x 91mm				
Performance	Strokes to attain maximum lift		13 full	
	Steering pivot range (degrees)		180°	
	Type of pump control - lift / release		Hand / Hand and Foot Release	
	Pallet entry assist type		Ramp	