



HAULER[®] 1200 SERIES

NEVER BE OUTLASTED.

The Hauler 1200 Series is equipped to handle any job within your facility. A large bed providing essential functionality can easily be converted for any task. Featuring integrated tie-downs, a 12 cubic-foot cargo bed, a full line of additional accessories and higher ground clearance with the Hauler 1200X, transporting tools and supplies has never been easier. Your work is unforgiving, expect nothing less than the best with the Hauler 1200 Series.

13.5 HP
EFI GAS

12 CU FT
CARGO BED

1500 LB / 1200 LB
TOWING CAPACITY

1200 LB / 900 LB
LOAD CAPACITY

HAULER® 1200 / SERIES



HAULER 1200

HAULER 1200X

OPTIONS & ACCESSORIES

- Limited Slip Differential
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- 15 cu-ft Aluminum Bed with L-Track System
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights
- LED Taillights/Brake Lights
- Ladder/Hoop Rack (Aluminum Bed Only)
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Standard Rear Receiver Hitch
- Fuel/Oil Gauge



(844) 432-4724

fairchildequipment.com

CUSHMAN.COM

HAULER 1200

HAULER 1200X

BODY & CHASSIS

| | | |
|----------------|--|--|
| FRAME | Welded Steel with E-Coat & DuraShield™ Powder Coat | |
| BODY & FINISH | Injection Molded TPO | |
| STANDARD COLOR | Forest Green | |

DIMENSIONS

| | | |
|-------------------------|---|--------------------|
| OVERALL LENGTH | 119 in (302 cm) | |
| OVERALL WIDTH | 49.4 in (125.5 cm) | |
| OVERALL HEIGHT W/CANOPY | 70.5 in (179.1 cm) | 77 in (195.6 cm) |
| WHEEL BASE | 76.8 in (195.1 cm) | 77.5 in (196.9 cm) |
| FRONT WHEEL TRACK | 35 in (88.9 cm) | 38.0 in (96.5 cm) |
| REAR WHEEL TRACK | 38.5 in (97.8 cm) | |
| GROUND CLEARANCE | 3.5 in (8.9 cm) | 7 in (17.8 cm) |
| CARGO BOX CAPACITY | 12 cu ft (0.34 cu m) | |
| CARGO BOX DIMENSIONS | 39 in (L) x 44 in (W) x 12 in (D) (99 cm x 111.8 cm x 30.5 cm) | |
| CARGO BOX MATERIAL | Roto-Molded Polyethylene | |

POWER

| | | |
|--------------------|--|--|
| POWER TRAIN | 4-Cycle, 24.5 cu in (401cc) | |
| VALVE TRAIN | Single Cylinder OHV | |
| HORSEPOWER (KW) | 13.5 hp (10.1 kW) | |
| ELECTRICAL SYSTEM | Starter/Generator, Solid State Reg. | |
| BATTERY (QTY/TYPE) | One, 12V Maintenance Free | |
| KEY OR PEDAL START | Pedal | |
| AIR CLEANER | Replaceable Industrial Rated Dry Cartridge | |
| LUBRICATION | Pressurized Oil System | |
| OIL FILTER | Spin-On | |
| COOLING SYSTEM | Air Cooled | |
| FUEL CAPACITY | 6.65 Gallon (25 L) tank | |
| DRIVE TRAIN | Continuously Variable Transmission | |
| TRANSAXLE | Differential w/ Helical Gears | |
| GEAR SELECTION | Forward - Reverse | |
| REAR AXLE RATIO | 11.47: 1 (Forward) 14.35:1 (Reverse) | |

PERFORMANCE

| | | |
|--------------------------|--|--|
| SEATING CAPACITY | 2-Person | |
| CURB WEIGHT | 980 lb (445 kg) | 1003 lb (455 kg) |
| BED LOAD CAPACITY | 800 lb (363 kg) | 500 lb (227 kg) |
| VEHICLE LOAD CAPACITY | 1200 lb (545 kg) | 900 lb (408 kg) |
| SPEED | 14.5 mph ± 0.5 mph (23.3 kph ± 0.8 kph) | 16.5 mph ± 0.5 mph (26.6 kph ± 0.8 kph) |
| TOWING CAPACITY | 1500 lb (680 kg) max | 1200 lb (544 kg) max |
| OUTSIDE CLEARANCE CIRCLE | 21.5 ft (6.6 m) | 23.5 ft (7.2 m) |

STEERING & SUSPENSION

| | | |
|----------------------|---|---------------------------|
| STEERING | Self-Compensating Rack & Pinion | |
| SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers | |
| SERVICE BRAKE | Dual Rear Wheel Mechanical, Self-Adjusting Drum | |
| PARKING BRAKE | Self-Compensating, Single-Point Engagement | |
| TIRES (FRONT & REAR) | 18 x 8.5 - 8 (6 - Ply Tires) | 20 x 8-10 (6 - Ply Tires) |