

ELITE SERIES

EXPERIENCE SUPERIOR PERFORMANCE.

Reach the full potential of your workday with the Hauler PRO Series. With a zero-maintenance ELiTE lithium powertrain activated by Samsung SDI battery technology, the Hauler PRO Series has the power to get the job done, all while providing the benefits of zero-maintenance batteries and lower operational costs.




ZERO Maintenance

ELITE LITHIUM BATTERY

1500 LB / 1200 LB TOWING CAPACITY

1200 LB / 900 LB LOAD CAPACITY

12 CU FT CARGO BED







HAULER PRO ELITE

HAULER PRO-X ELITE

ELITE LITHIUM POWERTRAIN

- Zero Maintenance
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Standard Limited Slip Differential
- Standard Automatic Park Brake
- Multifunction SOC/Speedometer Gauge

OPTIONS & ACCESSORIES

- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- 15 cu-ft Aluminum Bed with L-Track System
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights
- LED Taillights/Brake Lights
- Ladder/Hoop Rack (Aluminum Bed Only)
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Standard Rear Receiver Hitch
- Hour Meter
- Rapid On-Board Charger

(844) 432-4724

fairchildequipment.com

HAULER® PRO / ELITE SERIES

HAULER PRO ELITE HAULER PRO-X ELITE

BODY & CHASSIS

FRAME Welded Steel with E-Coat & DuraShield™ Powder Coat

BODY & FINISH Injection Molded TPO

STANDARD COLOR Forest Green

DIMENSIONS

OVERALL LENGTH 119 in (302 cm) OVERALL WIDTH 49 in (125 cm) OVERALL HEIGHT W/CANOPY 70.5 in (179.1 cm) 77 in (196 cm) 77.5 in (196.9 cm) WHEEL BASE 76.8 in (195 cm) FRONT WHEEL TRACK 35 in (88.9 cm) 38.0 in (96.56 cm) REAR WHEEL TRACK 38.5 in (97.8 cm) GROUND CLEARANCE 4.3 in (11 cm) 5.5 in (14 cm) CARGO BOX CAPACITY 12 cu ft (0.34 cu m) 39 in (L) x 44 in (W) x 12 in (D) CARGO BOX DIMENSIONS (99 cm x 111.8 cm x 30.5 cm) CARGO BOX MATERIAL Roto-Molded Polyethylene

POWER

POWER SOURCE 56.7V Li-Ion Battery AC Induction MOTOR TYPE HORSEPOWER (KW) 14.9 hp (11.1 kW) 48V Primary, 12V Auxiliary **ELECTRICAL SYSTEM** 4.2 ELiTE - Twin Pack BATTERY (QTY/TYPE) **BATTERY CHARGER** 811 Watt World Charger KEY OR PEDAL START Pedal DRIVE TRAIN Motor Shaft Direct Drive TRANSAXLE Limited-Slip Differential with Helical Gears SPEED CONTROLLER 350 Amp AC Controller GEAR SELECTION Dash Mounted Forward-Neutral-Reverse / Key Switch REAR AXLE RATIO 16.99:1

PERFORMANCE

SEATING CAPACITY 2-Person CURB WEIGHT 926 lb (420 kg) 971 lb (440 kg) **BED LOAD CAPACITY** 800 lb (363 kg) 500 lb (227 kg) VEHICLE LOAD CAPACITY 1200 lb (544 kg) 900 lb (408 kg) SPEED $16.5 \text{ mph} \pm .05 \text{ mph} (26.5 \text{ kph} \pm 0.8 \text{ kph})$ TOWING CAPACITY 1500 lb (680 kg) max 1200 lb (544 kg) max **OUTSIDE CLEARANCE CIRCLE** 21.5 ft (6.6 m)

STEERING & SUSPENSION

STEERING Self-Compensating Rack & Pinion

SUSPENSION Leaf Springs w/ Hydraulic Shock Absorbers

SERVICE BRAKE Dual Rear Wheel Mechanical, Self-Adjusting Drum

PARKING BRAKE Automatic Electro-Magnetic

TIRES (FRONT & REAR) 18 × 8.5 - 8 (6 - Ply Tires) 20 × 8-10 (6 - Ply Tires)



