



SHUTTLE™ 2+2

VERSATILITY COMMANDS THE DAY.

The newly redesigned Shuttle 2+2 is the ideal choice for transporting personnel and visitors. Comfortably seating up to four passengers with bench seats, the rear seat will also convert to a cargo deck. The Shuttle 2+2 is offered in your choice of a fuel-efficient 13.5-hp EFI gas engine or with an ELITE lithium powertrain activated by Samsung SDI lithium technology.

ELITE
LITHIUM

ALL-NEW
IMPROVED STYLING

NOW AVAILABLE WITH
ELITE LITHIUM
POWERTRAIN

18" OR 20"
TIRE OPTIONS

2 OR 4-WHEEL
MECHANICAL BRAKE
OPTIONS



STANDARD FEATURES

- RFS Pro Rear-Facing Seat
- Halogen Headlights
- 18" or 20" Tires
- 2-Wheel Mechanical Brakes
- E-Shield™ Frame
- Modular Canopy
- Premium Steering Wheel
- Side Body Color
- Multifunction Gauge (ELiTE only)
- Fuel and Oil Gauge (Gas only)

OPTIONS & ACCESSORIES

- 4-Wheel Mechanical Brakes
- Contoured Seats
- Limited Slip Differential
- LED Headlights, Taillights and Brake Lights
- Brush Guard
- Lockable Glove Box with Shelf and Molded Rubber Mats
- Fold-Down Windshield
- Flat Windshield
- Weather Enclosure
- USB Outlet
- Rearview Mirror
- ELiTE Lithium 2.2, 4.2, or 6.2 Pack (ELiTE only)
- Rapid On-Board Charger (ELiTE only)



(844) 432-4724

fairchildequipment.com

CUSHMAN.COM

SHUTTLE™ 2+2

SHUTTLE 2+2 ELITE

SHUTTLE 2+2 GAS

18" TIRES

20" TIRES

18" TIRES

20" TIRES

BODY & CHASSIS

FRAME Welded Steel with E-Coat & DuraShield™ Powder Coat

BODY & FINISH Injection Molded TPO

STANDARD COLOR Patriot Blue

DIMENSIONS

| | | | | |
|-----------------------------|--|----------------|----------------|----------------|
| OVERALL LENGTH | 113 in (287 cm) | | | |
| OVERALL WIDTH | 47 in (119 cm) | | | |
| OVERALL HEIGHT (W/ CANOPY) | 76 in (193 cm) | 80 in (203 cm) | 76 in (193 cm) | 80 in (203 cm) |
| OVERALL HEIGHT (W/O CANOPY) | 48 in (122 cm) | 52 in (132 cm) | 48 in (122 cm) | 52 in (132 cm) |
| WHEEL BASE | 65.5 in (166 cm) | | | |
| WHEEL TRACK | 37 in (94 cm) Front / 38 in (97 cm) Rear | | | |
| GROUND CLEARANCE | 4.3 in (11 cm) | 5.5 in (14 cm) | 4.3 in (11 cm) | 5.5 in (14 cm) |

POWER

| | | |
|--------------------|---|--|
| POWER SOURCE | 56.7V Li-Ion Battery | 4-Cycle, 24.5 cu in (401cc) |
| VALVE TRAIN | N/A | Single Cylinder OHV |
| HORSEPOWER (KW) | 11.7 hp (8.7 kW) | 13.5 hp (10.1 kW) |
| ELECTRICAL SYSTEM | 48V Primary, 12V Auxiliary | Starter/Generator, Solid State Regulator |
| BATTERY (QTY/TYPE) | 2.2 Single, 56.7V Li-Ion Composite Module | One, 12V Maintenance Free |
| BATTERY CHARGER | 56.7V, 350W Domestic Charger, 3M Charging Cord | N/A |
| KEY OR PEDAL START | Pedal | |
| AIR CLEANER | N/A | Industrial Rated Dry Filter |
| LUBRICATION | N/A | Pressurized Oil System |
| OIL FILTER | N/A | Spin-On |
| COOLING SYSTEM | N/A | Air Cooled |
| FUEL CAPACITY | N/A | 5.96 Gallon (22.6 L) tank |
| DRIVE TRAIN | Motor Shaft Direct Drive | Continuously Variable Transmission (CVT) |
| TRANSAXLE | Differential w/ Helical Gears | |
| GEAR SELECTION | Dash Mount Forward-Neutral-Reverse / Key Switch | Forward - Reverse |
| REAR AXLE RATIO | 16.99:1 | 11.47:1 (Forward) / 14.35:1 (Reverse) |

PERFORMANCE

| | | | | |
|--------------------------|---|-----------------|-----------------|-----------------|
| SEATING CAPACITY | 4-Person | | | |
| WEIGHT W/O BATTERIES | 743 lb (342 kg) | 782 lb (351 kg) | 872 lb (396 kg) | 913 lb (414 kg) |
| CURB WEIGHT | 790 lb (363 kg) | 829 lb (372 kg) | 902 (409 kg) | 963 lb (437 kg) |
| VEHICLE LOAD CAPACITY | 800 lb (363 kg) | | | |
| OUTSIDE CLEARANCE CIRCLE | 18.9 ft (5.76 m) | | | |
| SPEED | 16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph) | | | |

STEERING & SUSPENSION

| | | | | |
|----------------------|--|------------------------|------------------|------------------------|
| STEERING | Self-Compensating Rack and Pinion | | | |
| SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers | | | |
| SERVICE BRAKE | Dual Rear Wheel Mechanical Self-adjusting Drum | | | |
| PARKING BRAKE | Self-Compensating, Single-Point Engagement | | | |
| TIRES (FRONT & REAR) | Hole-N-One Tires | K399, 205/65-10, 6 Ply | Hole-N-One Tires | K399, 205/65-10, 6 Ply |

Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model. California state law prohibits the sale of Model Year 2024 and later gas-powered carts. ©2023 Textron Specialized Vehicles Inc. 60009-G8 (Rev. 05/2023)

