



SHUTTLE™ 6

ACCELERATE GROUP TRANSPORTATION.

Comfortably and effectively move up to six people with the use of the four forward-facing seats and two rear-facing seats in the Shuttle 6.

Available as an ELiTE lithium vehicle activated by Samsung SDI battery technology or with an efficient 13.5 hp EFI gas engine, the Shuttle 6 gives you the ability to take care of every task across your facility.

ELiTE
LITHIUM

ELiTE LITHIUM
OR
13.5 HP
EFI GAS

AUTOMATIC
PARK BRAKE
(ELiTE ONLY)

1200 LB
VEHICLE LOAD CAPACITY



ELITE LITHIUM POWERTRAIN

- Zero Maintenance
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Standard Limited Slip Differential
- Standard Automatic Park Brake

OPTIONS & ACCESSORIES

- Rearview Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Turn Signal with Four-Way Flashers
- LED Headlights
- LED Taillights/Brake Lights
- Wheel Covers
- Additional Body Colors
- Rapid On-Board Charger (ELITE Only)
- ELITE World Charger (ELITE Only)
- CE Kit (Gas Only)



(844) 432-4724

fairchildequipment.com

CUSHMAN.COM

SHUTTLE™ 6

SHUTTLE 6 ELITE

SHUTTLE 6 GAS

BODY & CHASSIS

| | | |
|----------------|--|--|
| FRAME | Welded Steel with E-Coat & DuraShield™ Powder Coat | |
| BODY & FINISH | Injection Molded TPO | |
| STANDARD COLOR | Patriot Blue | |

DIMENSIONS

| | | |
|------------------|---|----------------|
| OVERALL LENGTH | 134 in (343 cm) | |
| OVERALL WIDTH | 48.5 in (123 cm) | |
| OVERALL HEIGHT | 48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof) | |
| WHEEL BASE | 93.5 in (237 cm) | |
| WHEEL TRACK | 34.2 in (87 cm) Front / 38.0 in (97 cm) Rear | |
| GROUND CLEARANCE | 3.9 in (9.8 cm) | 4.3 in (11 cm) |

POWER

| | | |
|--------------------|---|--|
| POWER SOURCE | 56.7V Li-Ion Battery | 4-Cycle, 24.5 cu in (401cc) |
| VALVE TRAIN | N/A | Single Cylinder OHV |
| HORSEPOWER (KW) | 14.9 hp (11.1 kW) | 13.5 hp (10.1 kW) |
| ELECTRICAL SYSTEM | 48V Primary, 12V Auxiliary | Starter/Generator. Solid State Reg. |
| BATTERY (QTY/TYPE) | 56.7V Li-Ion Composite Module + Cell Model | One, 12V Maintenance Free |
| BATTERY CHARGER | 56VDC, 120/230 VAC, UL/CSA, CE | N/A |
| KEY OR PEDAL START | | Pedal |
| AIR CLEANER | N/A | Replaceable Industrial Rated Dry Cartridge |
| LUBRICATION | N/A | Pressurized Oil System |
| OIL FILTER | N/A | Spin-On |
| COOLING SYSTEM | N/A | Air Cooled |
| FUEL CAPACITY | N/A | 5.96 Gallon (22.6 L) tank |
| DRIVE TRAIN | Motor Shaft Direct Drive | Continuously Variable Transmission |
| TRANSAXLE | Limited-Slip Differential with Helical Gears | Differential w/ Helical Gears |
| GEAR SELECTION | Dash Mount Forward-Neutral-Reverse / Key Switch | Forward - Reverse |
| REAR AXLE RATIO | 16.99:1 | 11.47:1 (Forward) / 14.35:1 (Reverse) |

PERFORMANCE

| | | |
|--------------------------|---|---------------------------------------|
| SEATING CAPACITY | 6-Person | |
| WEIGHT W/O BATTERIES | 945 lb | 1124 lb (510 kg) |
| CURB WEIGHT | 1026 lb | 1164 lb (528 kg) |
| VEHICLE LOAD CAPACITY | 1200 lb (544 kg) | |
| OUTSIDE CLEARANCE CIRCLE | 25.5 ft (7.8 m) | |
| SPEED | 16.5 mph ± 0.5 mph (26.4 kph ± 0.8 kph) | 14 mph ± 0.5 mph (22.5 kph ± 0.8 kph) |

STEERING & SUSPENSION

| | | |
|----------------------|---|--|
| STEERING | Self-Compensating Rack and Pinion | |
| SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers | |
| SERVICE BRAKE | Rear Wheel Mechanical Self-Adjusting Drum | |
| PARKING BRAKE | Automatic Electro-Magnetic | Self-Compensating, Single-Point Engagement |
| TIRES (FRONT & REAR) | 18 x 8.50 - 8 (4 Ply Rated) | |