30AM CCESSMASTER® PUSH-AROUND VERTICAL





KEY SPECS

Platform Height 29.7-ft / 9.05-m

Platform Capacity 300-lb / 136-kg

Machine Width 29.1-in / 74-cm

Weight* 1,030-lb / 467-kg - AC 1,110-lb / 503-kg - DC

KEY FEATURES

- Ideal choice for a low-cost solution to overhead work and maintenance applications.
- Optimum operator comfort and stability with the most rigid mast in the industry.
- Improved maneuverability thanks to six-wheel design.
- More productivity with long battery duty cycles and an automatic charger.

ACCESSORIES & OPTIONS

- 12V 100Ah AGM Battery
- 22 x 22-in Gullwing Platform
- 26 x 26-in Right Side Entry Platform
- Auxiliary Lowering
- Amber Beacon
- Crane Hook

- Flourescent Tube Caddy
 - Locking Casters
 - Programmable 4-Digit Security Lock
 - Tool Tray 8 x 18 x 5-in (20 x 46 x 13-cm)

STANDARD SPECIFICATIONS

Performance	Indoor Only
Platform Height	29.7-ft / 9.05-m
Working Height	35.7-ft / 10.88-m
Platform Capacity	300-lb / 136-kg
Distance to Wall (Front)	9.5-in / 24.13-cm
Distance to Wall (Side)	20.5-in / 52.07-cm
Weight (AC)*	1,030-lb / 467-kg
Weight (DC)*	1,110-lb / 503-kg
*Certain options or country standards increase weight	
Power Source	

Batteries 12V 93 Amp hr (DC Only) Battery Charger Automatic (DC Only) Drive System 4 Brush Direct Electric (Planetary Gear) Wheels Rear Drive Wheels 10 x 2-in / 25 x 5-cm Front Caster Wheels 6 x 2-in / 15 x 5-cm

STANDARD FEATURES

- 26 x 28-in (66 x 71-cm) —Gull-Wing Entry Platform
- 93 AH Lead-Acid Battery—DC Models Only
- 110 Volt Double Receptacle in Platform
- Auto Power Saver—Shuts Off Power When Idled
- Automatic Battery Charger—DC Models Only
 Quick-Change Platform Mounts
- Battery Discharge Indicator (BDI)
- Descent Alarm

- Hourmeter
- Lanyard Attachment Anchor for Body Harness
- Low Maintenance Anodized Mast With 5 Times the Life of Previous Models
- Non-Marking Tires
- Roller Loading Device: For Loading on Pickup Trucks

BOAM ACCESSMASTER® PUSH-AROUND VERTICAL

/ERTICAL MAST LIFT



DIMENSIONS

All dimensions are approximate



Α.	Machine Height	78-in / 1.98-m
В.	Platform Width	28-in / 71-cm
C.	Platform Length	26-in / 66-cm
۵.	Machine Width	29.1-in / 74-cm
Е.	Machine Length	51.9-in / 1.31-m
	Machine Length without Battery Pack	47-in / 1.19-m
F.	Ground Entry Height	18.9-in / 48-cm
F.	Ground Entry Height	18.9-in / 48-cm





(844) 432-4724 fairchildequipment.com



We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.



JLG INDUSTRIES, INC. Toll-free US 877-JLG-LIFT JLG.com

An Oshkosh Corporation Company