38AM PUSH-AROUND VERTICAL





KEY SPECS

Platform Height 38-ft / 11.58-m

Platform Capacity

300-lb / 136-kg

Machine Width 29.1-in / 74-cm

Weight*

1,265-lb / 574-kg - AC 1,395-lb / 633-kg - DC

KEY FEATURES

- Ideal choice for a low-cost solution to overhead work and maintenance applications.
- Optimum operator comfort and stability with the most rigid mast in the industry.
- Improved maneuverability thanks to six-wheel design.
- More productivity with long battery duty cycles and an automatic charger.

ACCESSORIES & OPTIONS

- 12V 100Ah AGM Battery
- 22 x 22-in Gullwing Platform
- 26 x 26-in Right Side Entry Platform
- Amber Beacon
- Auxiliary Lowering
- Crane Hook

- Flourescent Tube Caddy
- Locking Casters
- Programmable 4-Digit Security Lock
- Tool Tray 8 x 18 x 5-in (20 x 46 x 13-cm)

STANDARD SPECIFICATIONS

Pertormance	indoor Uniy
Platform Height	38-ft / 11.58-m
Working Height	44-ft / 13.4-m
Platform Capacity	300-lb / 136-kg
Distance to Wall (Front)	15-in / 38.1-cm
Distance to Wall (Side)	24-in / 61-cm
Weight (AC)*	1,265-lb / 574-kg
Weight (DC)*	1,395-lb / 633-kg
*Certain options or country standards increase weight	
Power Source	
Batteries	12V 93 Amp hr (DC Only)
Battery Charger	Automatic (DC Only)
Drive System	4 Brush Direct Electric (Planetary Gear)
Wheels	
Rear Drive Wheels	10 x 2-in / 25 x 5-cm
Front Caster Wheels	6 x 2-in / 15 x 5-cm

Indoor Only

STANDARD FEATURES

- 26 x 28-in (66 x 71-cm) —Gull-Wing Entry Platform
- 93 AH Lead-Acid Battery—DC Models Only
- 110 Volt Double Receptacle in Platform
- Auto Power Saver—Shuts Off Power When Idled
- Automatic Battery Charger—DC Models Only
 Quick-Change Platform Mounts
- Battery Discharge Indicator (BDI)
- Descent Alarm

- Hourmeter
- Lanyard Attachment Anchor for Body Harness
- Low Maintenance Anodized Mast With 5 Times the Life of Previous Models
- Non-Marking Tires
- Roller Loading Device: For Loading on Pickup

38AM ACCESSMASTER® PUSH-AROUND VERTICAL

VERTICAL MAST LIFT



DIMENSIONS

All dimensions are approximate









(844) 432-4724 fairchildequipment.com



JLG INDUSTRIES, INC. Toll-free US 877-JLG-LIFT JLG.com

An Oshkosh Corporation Company



We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.