

450AJ

ARTICULATING BOOM LIFT

BOOM LIFT



KEY SPECS

Platform Height
45-ft / 13.72-m

Up and Over Height
24-ft / 7.3-m

Horizontal Outreach
25-ft / 7.62-m

Platform Capacity
550-lb / 250-kg

KEY FEATURES

- Improved multifunction capability for increased productivity.
- Provides durability and serviceability with DuraTough hood design.
- Delivers a zero calibration automatic load sensing system that eliminates the need to use external weights to calibrate the machine.
- Optimized 550-lb platform capacity for occupants and tools.

ACCESSORIES & OPTIONS

- 1/2-in Airline to Platform
- 43.5-lb Propane Tank
- AC Generator, 2500W
- Accessory Packages:
 - SkyGlazier® Package
 - SkyPower® Package
 - SkyWelder® Package
- Arctic Package¹
- Cold Weather Package²
- Hostile Environment Package³
- Hostile Environment Extreme Package⁴ (2WS Only)
- Light Package
- Platform Mesh to Mid or Top Rail
 - Aluminum or Plastic
- Platforms
 - Drop Bar, 30 x 36-in, 30 x 48-in, 30 x 60-in, 30 x 72-in
 - Fall Arrest, Rear Entry, 30 x 60-in
- Inward Self-Closing Swing Gate, 30 x 48-in, 30 x 60-in, 30 x 72-in
- SkySense® Enhanced Detection System
- Soft Touch
- Storage Tray - Center or Corner
- Tow Bar
- Welder Ready Package
- White Noise Alarm

1. Includes Arctic Hydraulic Hoses (Drive And Steer Only) And Main Boom Cable, Extreme Cold Engine Oil, Fuel Conditioner, Engine Block Heater, Battery Blanket, Glow Plugs, Hydraulic Tank Heater, Oversized Foot Switch and Arctic Hydraulic Oil.
2. Includes Battery Blanket, Hydraulic Tank Heater, Engine Block Heater Pad.
3. Includes Console Cover, Boom Wipers and Cylinder Bellows.
4. Hostile Environment Package Required; Includes Shields Over Turntable Swivel, Pinion Gear, Turntable Bearing, and Fire Resistant Wrap Over Drive and Steer Hoses.

STANDARD SPECIFICATIONS

Performance

| | |
|------------------------------|----------------------------------|
| Platform Height | 45-ft / 13.72-m |
| Horizontal Outreach | 25-ft / 7.62-m |
| Up and Over Height | 24-ft / 7.3-m |
| Swing | 355 Degrees Non-Continuous |
| Platform Capacity | 550-lb / 250-kg |
| Platform Rotator | 180 Degrees Hydraulic |
| Jib | 4-ft 1-in / 1.24-m |
| Range of Articulation | 145 Degrees (+76, -69) |
| Weight* | 14,150-lb / 6,418-kg |
| Max. Ground Bearing Pressure | 65 psi / 4.57 kg/cm ² |
| Drive Speed | 4.25 mph / 6.8 km/h |
| Gradeability 2WD / 4WD | 30% / 45% |
| Tilt Cut Out | 5 Degrees |
| Axle Oscillation | 4-in / 10-cm |
| Turning Radius Inside | 6-ft 9-in / 2.06-m |
| Turning Radius Outside | 15-ft 8-in / 4.78-m |

Engine

| | |
|---|-----------------|
| Dual Fuel – Kubota WG2503 | 60 hp / 44 kW |
| Diesel Fuel – Deutz D2.9L4 Tier 4 Final | 49 hp / 36.4 kW |
| Fuel Tank Capacity | 16 gal / 60.6 L |

Tires

| | |
|----------|--|
| Standard | Foam Filled, 33/1550 x 16.5 |
| Optional | Foam Filled Low Profile Non-marking, IN315/55D20 Foam Filled Low Profile, IN315/55D20 Foam Filled Non-marking, 12 x 16.5 Foam Filled, 12 x 16.5 or 33/1550 x 15.5 Foam Filled Turf & Sand, 33 x 16LL500 Solid Low Profile Non-marking, 33 x 12-20 |

Hydraulic System

| | |
|-----------------|-------------------|
| System Capacity | 17.3 gal / 65.5 L |
| Tank Capacity | 15 gal / 56.8 L |
| Auxiliary Power | 12V DC |

STANDARD FEATURES

- 4-ft 1-in (1.24-m) Articulating Jib
- 5 Degree Tilt Alarm/ Indicator Light
- 12V-DC Auxiliary Power
- 110V-AC Receptacle in the Platform
- Cast Aluminum Control Box
- ClearSky Smart Fleet™ Hardware (CS550)**
- Control ADE® System
- Four-Wheel Hydrostatic Drive
- Gull-Wing Turntable Hoods
- Horn
- Hourmeter
- LED Motion/Amber Beacon (CS550)**
- Improved Multi-Function Controls
- Lifting/Tie Down Lugs
- Load Sensing System
- Motion Alarm
- Oscillating Axle
- Platform Console Machine Status Light Panel
- Proportional Controls
- SkyGuard SkyLine™
- Swing-Out Engine Tray

*Certain Options or Country Standards Increase Weight.

**Standard Beacon and ClearSky Smart Fleet Hardware Availability Varies by Model Throughout 2023.

***Provides Indicator Lights at Platform Control Console for System Distress, Low Fuel, Degree Tilt Light and Foot Switch Status.

Not All Options Can Be Outfitted On the Same Machine; Consult Factory for Compatibility.
Additional Accessories and Options Available Via JLG Aftermarket.

450AJ


ARTICULATING BOOM LIFT

BOOM LIFT




DIMENSIONS

All dimensions are approximate



| | | |
|----|------------------|-----------------------|
| A. | Platform Width | 30-in / 0.76-m |
| B. | Platform Length | 72-in / 1.83-m |
| C. | Machine Width | 7-ft 8.6-in / 2.35-m |
| D. | Tailswing | Zero |
| E. | Machine Height | 7-ft 5.3-in / 2.27-m |
| F. | Machine Length | 21-ft 6.9-in / 6.57-m |
| G. | Wheelbase | 7-ft 9-in / 2.36-m |
| H. | Ground Clearance | 16.4-in / 41.7-cm |

REACH DIAGRAM



(844) 432-4724

fairchildequipment.com



We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.



JLG INDUSTRIES, INC.
Toll-free US 877-JLG-LIFT
JLG.com

An Oshkosh Corporation Company