K16 - Series Scrubbers











Poly 5/16" (7.9mm)

3/16" Steel (4.8mm) Powder Coated Steel Chassis Construction:

(2x) 10" x 2.5" (25.4 x 6.4cm) - Black

(2x) 2.5" x 1.38" (6.4 x 3.5cm) - Black

53 x 29 x 38.5 in *

135 x 74 x 98 cm*

cornigaration and squeegees removed from the macrime			9
Scrub Motor(s):	0.75 hp / 559 watts	1.5 hp / 1,100 watts	0.75 hp / 559 watts
Brush RPM:	270 rpm	2,500 rpm	270 rpm

24 VDC

175 ah WET

Up to 2.5 Hours 120VAC / 60 Hz Input - 24VDC / 12 amp Output

0.5hp - All Gear / Sealed (373 watts)

16 gal / 60 L

0 - 0.6 GPM / Stainless Inline (0 - 2.3 LPM)

16 gal / 60 L

0.8 hp / 3 Stage / 640 watts

0.8 hp / 36V / 3 Stage / 640 watts

37 in (94 cm) 37 in (94 cm) Squeegee:

66 dBA**

25,979 ft2/hr 28,000 ft2/hr 28,000 ft2/hr 25,979 ft2/hr 24,000 ft2/hr Productivity - Theoretical:*** 2,414 m2/hr 2,601 m2/hr 2,229 m2/hr 2,601 m2/hr 2,414 m2/hr 12,061 ft2/hr 13,000 ft2/hr 13,000 ft2/hr 12,061 ft2/hr 11,132 ft2/hr Productivity - Practical:*** 1,121 m2/hr 1,208 m2/hr 1,034 m2/hr 1,208 m2/hr 1,121 m2/hr



Tank Material:

Front Wheels (Diameter × Width):

Rear Casters (Diameter x Width):

Length x Width x Height

System Voltage:

Standard Battery:

Charger:

Battery Run Time:*

Traction Drive System:

Solution Tank Capacity:

Recovery Tank Capacity:

Solution Flow / Filter:

Vacuum Motor:

Sound Levels:**

Vacuum Water Lift:

Imported From Wisconsin - USA

*Battery Run Times are based on continuous scrubbing run times, standard batteries, low down