

# K19 - Series Scrubbers



	DUAL DISK		ORBITAL		CYLINDRICAL
					
	<b>26 in / 710 mm</b>	<b>28 in / 810 mm</b>	<b>24 in / 610 mm</b>	<b>28 in / 710 mm</b>	<b>26 in / 710 mm</b>
Tank Material:	Poly 5/16" (7.9mm)				
Chassis Construction:	3/16" Steel (4.8mm) Powder Coated Steel				
Front Wheels (Diameter x Width):	(2x) 10" x 2.5" (25.4 x 6.4cm) - Black				
Rear Casters (Diameter x Width):	(2x) 2.5" x 1.38" (6.4 x 3.5cm) - Black				
Length x Width x Height	53 x 29 x 38.5 in *				
<small>*Dimensions listed are for the largest width deck configuration and squeegees removed from the machine</small>	135 x 74 x 98 cm*				
Scrub Motor(s):	0.75 hp / 559 watts		1.5 hp / 1,100 watts		0.75 hp / 559 watts
Brush RPM:	270 rpm		2,500 rpm		270 rpm
System Voltage:	24 VDC				
Standard Battery:	175 ah WET				
Battery Run Time:*	Up to 3.5 Hours				
Charger:	120VAC / 60 Hz Input - 24VDC / 12 amp Output				
Traction Drive System:	0.5hp - All Gear / Sealed (373 watts)				
Solution Tank Capacity:	19 gal / 72 L				
Solution Flow / Filter:	0 - 0.6 GPM / Stainless Inline (0 - 2.3 LPM)				
Recovery Tank Capacity:	19 gal / 72 L				
Vacuum Motor:	0.8 hp / 36V / 3 Stage / 640 watts				
Vacuum Water Lift:	70" / 178 cm / 70 cfm				
Squeegee:	37 in (94 cm)	41 in (104 cm)		37 in (94 cm)	
Sound Levels:**	66 dBA**				
Productivity - Theoretical:***	25,979 ft <sup>2</sup> /hr 2,414 m <sup>2</sup> /hr	28,000 ft <sup>2</sup> /hr 2,601 m <sup>2</sup> /hr	24,000 ft <sup>2</sup> /hr 2,229 m <sup>2</sup> /hr	28,000 ft <sup>2</sup> /hr 2,601 m <sup>2</sup> /hr	25,979 ft <sup>2</sup> /hr 2,414 m <sup>2</sup> /hr
Productivity - Practical:***	12,061 ft <sup>2</sup> /hr 1,121 m <sup>2</sup> /hr	13,000 ft <sup>2</sup> /hr 1,208 m <sup>2</sup> /hr	11,132 ft <sup>2</sup> /hr 1,034 m <sup>2</sup> /hr	13,000 ft <sup>2</sup> /hr 1,208 m <sup>2</sup> /hr	12,061 ft <sup>2</sup> /hr 1,121 m <sup>2</sup> /hr

Specifications subject to change without notice.  
 \*Battery Run Times are based on continuous scrubbing run times, standard batteries, low down pressure and all options off.  
 \*\*Decibel levels for Disk per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

\*\*\*Productivity is based off of ISSA 2010 Cleaning Times



(844) 432-4724  
 fairchildequipment.com

