

ELECTRIC DUMPSTER | HTD-5E

Max carry capacity: 1,102 lbs Load over height: 4 ft. 9 in. Machine width: 2 ft. 4 in.



100% electric. Zero emissions.

JCB is leading the way in clean technology and reducing harmful emissions. That's why we are introducing JCB E-TECH, a new generation of electric products with zero emissions at point of use that don't compromise on performance. The compact, high-tip Electric Dumpster is designed to save time, energy and money.







LOW NOISE.

Low noise levels make the electric Dumpster ideal for urban areas and indoor use. This also allows better communication with co-workers.

A FULL DAYS SHIFT.

Lithium-ion batteries power the machine for a full typical work day, while conveniently offering 110-120V on-board charging capabilities.






SAFETY INNOVATION.

The new SmartStep feature offers increased safety and operator comfort. Stepping off isolates power to the tracks while still allowing use of the hydraulics and skip.

ZERO COMPROMISE.

The electric Dumpster has zero compromise on performance and has all the benefits of the traditional diesel equivalent.





STA	STATIC DIMENSIONS		
Α	Machine length (operating position)	mm (ft-in)	2151 (7-1)
В	Undercarriage length	mm (ft-in)	1166 (3-10)
С	Maximum height (tipping position)	mm (ft-in)	2720 (8-11)
D	Skip ground clearance (tipping position)	mm (ft-in)	1450 (4-9)
Е	Skip height (transport position)	mm (ft-in)	860 (2-10)
F	Overall height (transport position)	mm (ft-in)	1105 (3-7)
G	Track width	mm (ft-in)	180 (0-7)
Н	Inside track width	mm (ft-in)	339 (۱-۱)
-1	Maximum machine width	mm (ft-in)	706 (2-4)
	Step Height	mm (ft-in)	249 (0-10)
	Maximum approach angle (°)		12

WEIGHTS & CAPACITIES			
Machine weight	kg (lb)	606 (1336)	
Max. carrying capacity	kg (lb)	500 (1102)	
Max. operating weight (with load)	kg (lb)	1106 (2438)	
Hydraulic tank capacity	litres (gal)	14 (3.7)	

BATTERY CAPACITY			
Peak Power	kW	9	
Continuous Power	kW	4.5	
Peak Torque	ft-lb	42	
Battery Rating	kWh	4.9	
System Voltage	V	48	
Max. rpm		3150	

HYDRAULICS		
Pump number		3
Pump output	l/min (gal/min)	27 (6)
Operating pressure	bar (psi)	150 (2176)

UNDERCARRIAGE		
Number of bottom rollers		2
Track tensioning		Manual
Speed range	kph (mph)	0-3 (0-1.9)

STANDARD & OPTIONAL EQUIPMENT		
0.3m³ (0.4yd³) skip	•	
2 speed tracking	•	
SmartStep	•	

STANDARD • OPTIONAL +





100% electric. Zero emissions.

Your nearest JCB dealer



CUSTOMERS FOR LIFE (844) 432-4724

fairchildequipment.com

Electric Dumpster HTD-5E

Max carry capacity: 1,102 lbs Load over height: 4 ft. 9 in. Machine width: 2 ft. 4 in.

JCB North America

2000 Bamford Blvd., Pooler, Georgia, 31322 Tel: (912) 447-2000

Download the very latest information on this product range at www.jcb.com

JCB inc. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any other means, electronic, mechanical, application. Guidance and advice should always be sought from your JCB Dealer. JCB reserves the right to change specifications with out notice. Illustrations and specifications shown may include optional equipment and accessories. The JCB logo is a registered trademark of J C Bamford Excavators Ltd.









