

Columbia's Payloader PRO is built for work and comfort. With a focus on ergonomics, including an expanded operator area, tilt-adjust steering and fine-tuned pedal placement, the Payloader PRO ensures your team rides in style and comfort wherever they drive.

Redesigned with a coilover shock front suspension, the Payloader PRO will glide through your worksite without compromising towing and cargo capacities.

Payloader PRO comes standard with AC Drive to give you the torque you need to handle hills and grades with ease. With Smartphone connected controller, on-board diagnostics, battery discharge indicator, and optional telematics services, the Payloader PRO keeps your team connected and charged throughout their day!



- 1 Enhanced Turning Radius
- 2 12V and USB Charging Ports
- 3 Tilt-Adjust Steering Wheel





BUILT FOR WORK




Dimensions

Step Height: 14.5 in.
Load Bed Height: 27.5 in.
Ground Clearance: 4.5 in.







Performance	Standard Duty	Heavy Duty
Max Speed Forward:	14 MPH	
Turning Radius:	122 in.	
Range ¹:	Up to 30 miles	
leight & Capacit	v	
Vehicle Weight:	2 pass. 1,865 lbs. 4 pass. 1,960 lbs.	2 pass. 1,915 lbs. 4 pass. 2,010 lbs.
Rated Capacity 2:	2,000 lbs.	3,000 lbs.
Towing Capacity 3:	6,500 lbs.	10,000 lbs.
Power Train		
Motor:	5kW AC Induction motor w/ parking brake	8kW AC Induction motor w/ parking brake
Batteries:	Eight 6-volt, heavy duty, 232 amp hour deep cycle	
Charger:	Built-in, micro-processor control, fully sealed, anti-drive away interlock, 110-240 VAC, 50 / 60 HZ	
Controller Type:	Programmable, solid state, reduced speed reverse with diagnostic LED & calibrator interface	
Controller Rating:	440 amp	
Motor Braking Mode:	Regenerative with top speed limiting	
Directional Control:	Dash-mounted safety directional rocker switch	
Drive Unit/Differential:	Direct drive, automotive differential, 12.62:1 drive ratio	Direct drive, automotive differential, 16.67:1 drive rati
Body		
Passenger Capacity:	Two with up to four (optional 2nd row seat)	
Seating:	Front row: bucket seats with arm rests, driver side adjustable; 2nd row: bench seats	
Body:	Welded heavy duty; 12-gauge structural steel smooth plate body; steel powder coated bulkhead	
Lighting:	Dual recessed LED headlights; LED tail and brake lights; reverse lights	
Accessories:	Multifunctional display with digital speedometer, battery discharge indicator & hour meter; DC/DC converter; high/low speed switch; cup holders; passenger side storage pocket; USB and 12v accessory power; reverse warning alarm; driver seat power interlock switch	
Chassis		
Frame:	Unitized, powder coated smooth plate steel, 1/4" thick structure	
Steering:	Tilt adjust automotive steering wheel to gearbox	
Brakes:	Rear-wheel hydraulic drum brakes, automatic parking brake	4-wheel hydraulic, front discs, rear drums, automatic parking brake
Brakes: Suspension:		automatic parking brake

Features, options, specifications, color availability and model designation are subject to change without notice. Some vehicles are pictured with options that may be available at extra cost or may not be available on some models. Ask your dealer about the availability of options and verify that the vehicle you order includes the equipment you require.

1 Range will vary depending on temperature, grade, payload and driving style. | 2 Rated Capacity Includes personnel, cargo, options and accessories.

3 Towing Capacity is rolling load that the vehicle can tow on a flat / level surface.

All specifications are subject to change without notice.

Columbia Vehicle Group, Inc.







COLUMBIA TOMBERLIN