



5.5K SERIES

FORKLIFT

Technical Specifications

5.5K-M Donkey

| | |
|-------------------------|---------------------|
| Mast Type | Fixed Mast |
| Capacity | 5500 |
| Diesel Engine | 50 HP |
| Engine Emission | Tier 4 |
| Max RPM | 2750 |
| Electrical System | 12 Volt |
| Drive Tires | 31" |
| Steering | 29" |
| Hydraulic Cylinder | Steer Cylinder |
| Max Speed | 15 MPH |
| Max Grad-ability | 32% |
| Ready to Operate Weight | 5150 |
| Mast Tilt | 8 degrees/7 degrees |
| Side Shift | 4" |
| Forks | 48" |
| Scissor Reach | 44" STD/56" EXT |
| Height to Top of Canopy | 90" |
| Load Spacing-Frame | 64" |
| Overall Width | 94" |
| Overhang | 58" |
| Lift Height | 120"/144" Two Stage |
| Mast Raided Height | 185"/209" |
| Mast Height Collapsed | 112"/124" |
| Ground Clearance | 10" |



**The only truck-mounted
Single Axle Solution®**



**The longest standard
reach in the industry**



**The lightest, fastest,
most versatile forklift in
the industry**



**Centralized weight
distribution**



**Lowest ground pressure
(LGP) of any forklift on
the market**



(844) 432-4724
fairchildequipment.com

★★★★★
MADE IN THE USA